

# Guidelines for the Cleaning of euro-flex™ high wet slip resistant tile

I. Procedure for Initial Deep Cleaning after Installation of New Flooring and before putting new Flooring into Service.

#### **Equipment Needed:**

- Taski ErgoDisc 300 Floor Machine
- Taski ErgoDisc 300 Pad Holder
- Taski ErgoDisc Solution Tank
- Taski 18" Contact Pad or Taski 17" Purple Cleaning Pad
- Taski 17" Mint Polishing Pads
- Taski Profi Neutral Degreaser
- 2 each Mop Buckets & 1 Mop Wringer
- 2 each Mop-handles & Mops (clean)

### **Procedure for Initial Deep Cleaning**

- 1. Sweep or dust mop the entire area to be cleaned.
- 2. Mix Taski Profi in the ErgoDisc Solution Tank (installed on the ErgoDisc 300)6- 8 ounces of Profi to 1 gallon of water.
  - Use the machine as the dispensing system to apply the mixed Profi on the floor to be cleaned.
  - It is best to apply the Profi wet enough so that it will not dry as you wait approximately 5 -10 minutes for the Profi to emulsify the soil.
  - Apply in small manageable areas such as a 15' x 15' area may work best.
  - Do not allow the Profi to dry on the floor.
  - (Profi can be mopped on the surface of the floor if a chemical solution tank is not available.)
- 3. Scrub the area to be cleaned with the ErgoDisc using an 18" Taski Contact Pad or 17" Taski Purple Pad. After scrubbing a dirty slurry should be apparent.
- 4. Pick up the slurry with a mop and mop bucket or with a wet/dry vacuum. (use the 1st bucket)
- 5. Rinse the floor with water in the 2nd bucket using a 2nd Mop and Mop handle.
- 6. Additional rinsing may be necessary if the floor is very dirty.
- 7. Move on to the next area to be cleaned, repeat steps 2-6
- 8. After the entire floor has been cleaned and rinsed and dried, apply 2-3 coats of Taski Vision Matte Finish (formerly Taski Ombra) (1 gall/2000-2500 sft.) in thin layers with mopping equipment or a finish applicator.
- 9. Let dry between coats.

Note: Vision Matte (formerly Taski Ombra) provides a low satin luster. Vision Matte is very detergent resistant when cleaned with neutral, non- film forming detergent Stride Cleaner (formerly Taski R-50). It is not required to buff Taski Ombra.

1



## II Regular Maintenance Procedure for euro-flex™ Low Wet Slip Flooring

Dust mop daily and damp mop with neutral, non-film forming Stride Cleaner (formerly Taski R-50) in ½-2ozs./gall. of water.

Without rinsing these detergents will clean the floor surface and leave no film.

Re apply 1-2 coats of Taski Vision Matte Finish in 6 months intervals.

**DO NOT WAX** Low Wet Slip Resistant Flooring – This could cause loss of slip resistant properties

## Note:

The Taski Company was sold to Johnson Diversey. Johnson Diversey offers very limited distribution of our preferred cleaning chemicals.

## **Sourcing for Taski Products:**

Glasby Maintenance Supply Co., Pat Glasby 116 E. Orangethorpe Avenue Anaheim, CA 92806 +1 (714) 738-5121 Fax +1 (714) 447-8854 e-mail glasby@ix.netcom.com

### For your convenience Small Quantities are kept in stock by:

Tek Stil Concepts, Inc.
430 Lowy Drive
Chatsworth, GA 30705
+1 (706) 517-3599 alternate +1(800) 603-0848
Fax +1 (706) 517-1975
e-mail juergenb@ix.netcom.com

SKU	Description	Selling unit Case	Cost FOB
			Chatsworth, GA
2619-01	Taski Profi Degreaser Cleaner	4 x 1 gallon	\$ 130.00
2612-01	Stride Cleaner (replaces R-50 non film forming neutral detergent)	4 x 1 gallon	\$ 57.00
2611-05	Taski Vision Matte Finish	5 gallon bag in box	\$ 171.00

Note: Prices are subject to change due to increases by the manufacturer.