



Universal Pressure Sensitive Adhesive UZIN KE 2000 S

General:

Wet-bond, pressure-sensitive or contact dispersion adhesive with very high bond strength for resilient floor coverings. Ready to use, very easy to apply, very economical, long open time, high strength, excellent plasticiser resistance. Suitable for homogeneous and heterogeneous PVC and cushioned vinyl coverings, including design flooring, rubber floor tiles up to 2.5 mm and sheet rubber up to 3.5 mm thickness. Polyolefin coverings up to 2.5 mm thickness, textile flooring with PVC- or PU-foam backings, wall-coverings and resilient insulating underlays. Universal use as wet/semi-wet adhesive on absorbent substrates. On non-absorbent substrates (e.g. non absorbent underlays or UZIN KR 410) as a pressure-sensitive adhesive with a long drying time, e.g. for PVC/CV covering. Can also be used for contact or double-drop method. Suitable for areas exposed to castor wheels, in heavy-duty commercial and industrial locations. Interior use only. Solvent-free.

Storage:

Shelf life minimum 12 months in cool and dry storage conditions. For the production date, refer to the batch number label (dd,mm,yy). Protect against frost.

Technical Data:

Processing temperature: $\geq 15^{\circ}\text{C}$ at ground level

Relative humidity: $\leq 75\%$

Drying time: 20 – 40 minutes*

Laying time: 1 – 2 hours

Loadable: after 24 – 48 hours*

Set to Final Strength: 4 – 5 days*

Weld joints: after 24 – 48 hours*

*At 20°C and 65% relative humidity.

Tek Stil Concepts, Inc., Box 67, Haddonfield, NJ 08033 Phone 856-428-4464
800-603-0848 Fax 856-429-6532 juergenb@ix.netcom.com
www.tekstilconcepts.com



Backing Types:

Trowel Notch:

Consumption:

Smooth	23/80	150 – 170 sqft per gal.
Slightly embossed	23/80	150 – 170 sqft per gal.
Rubber, PO	23/80	150 – 170 sqft per gal.
PVC on PVC	23/80	150 – 170 sqft per gal.



Surface:

The surface must be resistant, level, dry, free of cracks, clean and free from materials which would impair adhesion. Prime and smooth surfaces which are not level, rough, non-absorbent or sensitive to dampness. You will find priming and smoothing materials in the UZIN Product Guide.

Application:

Apply adhesive with a suitable toothed spatula evenly to the surface and allow to dry. Only apply as much adhesive as can be covered within the laying time. Lay the flooring within the laying time and sand. Use water for the removal of fresh adhesive residue. Seal flooring seams at the earliest 24 hours, if possible, 2 – 3 days after laying.

Please refer to the separate UZIN Product Data Sheets, the installation instructions issued by the covering manufacturer as well as all applicable, national regulations and standards. No guarantee can be given for completed work. If in doubt, conduct your own test or trial.